



RAIMONDI

DAL 1974 INNOVAZIONI PER I
PROFESSIONISTI DELLA POSA
SINCE 1974 INNOVATIONS FOR
THE TILE SETTING PROFESSIONAL



JOLLYNA

Jollatrice da cantiere per eseguire taglio angolare a 46° ("jolly") su piastrelle di lunghezza fino a 120 cm
Compact machine to perform 46° bevels cut ("jolly") on tiles up to 120 cm (47 1/4") length

Progettata specificatamente per eseguire smussi a 46° ("jolly"), Jollyna risolve questo problema in modo semplice e con risultati perfetti.
Jollyna è un alleato formidabile per ottenere finiture di alto pregio direttamente in cantiere.

*Specifically designed to perform 46° bevels/angle cuts ("jolly"), Jollyna solves this problem in a simple way and with perfect results.
Jollyna is a formidable ally for obtaining high quality finishing directly on the job-site.*



RAIMONDI


JOLLYNA



DISCHI APPLICABILI AVAILABLE BLADES



CARATTERISTICHE TECNICHE - TECHNICAL CHARACTERISTICS



OPTIONAL ACCESSORIES



IMBALLI PACKAGE



- "Jollatrice" compatta per eseguire smussi a 46° ("jolly") su piastrelle di lunghezza massima 120 cm.
- Larghezza massima consigliata piastrella:
80 cm con estensione piano lavoro opzionale (art. 431EP01A);
35 cm in configurazione standard (senza piano di lavoro opzionale).
- Massimo spessore piastrella: 20 mm.
- Raffreddamento disco con pompa tramite spruzzo multigetto.
- Estensioni laterali piano di lavoro smontabili e gambe telescopiche per minimizzare gli ingombri ed agevolare il trasporto.
- Altezza e profondità gruppo motore regolabile per calibrazione fine della bisellatura 46° ("jolly").
- Fornita con disco diamantato Ø 200 mm, kit chiavi, pietra ravviva disco, manuale uso e manutenzione.

- Compact machine to perform 46° bevels cut ("jolly") on tiles up to 120 cm (47 1/4") length.
- Maximum recommended tile width:
80 cm (31 1/2") when equipped with table side extension (accessory part no. 431EP01A);
35 cm (13 3/4") in standard configuration (without side extension).
- Maximum tile thickness: 20 mm (3/4").
- Superior blade water-cooling (double-jets) with pump.
- Dismountable lateral table extensions and telescopic legs for easy transport.
- Motor has micrometric height and depth adjustment for fine adjustment of the 46° bevel ("jolly").
- Supplied with continuous rim diamond disc Ø 200 mm (8"), key kit, sharpening stone, use and maintenance manual.

MODELLI E SPECIFICHE - MODEL SPECIFICATIONS

| Codice Part no. | Barcode | ⚡ | Ⓜ | 🌀 | 🌀 | 🌀 | 🌀 | 🌀 | 🌀 | |
|-------------------|---------------|-----------|----------|--------------|--------|--------|------|--------|----|------|
| 431J2015EU | 8024648091086 | 230V 50Hz | monofase | single-phase | 1,5 HP | 1.1 kW | 2800 | 200 mm | 8" | 2800 |
| 431J2015BR | 8024648094865 | 230V 60Hz | monofase | single-phase | 1,5 HP | 1.1 kW | 3360 | 200 mm | 8" | 3360 |
| 431J2015US | 8024648094889 | 110V 60Hz | monofase | single-phase | 1,5 HP | 1.1 kW | 2800 | 200 mm | 8" | 2800 |
| 431J2015GB | 8024648094872 | 110V 50Hz | monofase | single-phase | 1,5 HP | 1.1 kW | 3360 | 200 mm | 8" | 3360 |

PRESTAZIONI E DIMENSIONI / PESI - PERFORMANCES AND DIMENSION / WEIGHT

| Modello Model | 🌀 | 📏 | 📏 | 📏 | 📏 | 📏 | 📏 | 📏 | 📏 | | |
|-----------------|--------------|---|--|--|---|---|--------------------|---|--------------------------------------|---|------------------|
| JOLLYNA | 200 mm 8" | Lunghezza di taglio max Max length of cut 120 cm 47 1/4" | Larghezza max piastrella Max tile width 80 cm 31 1/2" | Max spessore di taglio Max depth of cut 20 mm 1 3/16" | Minimo ingombro Size in transport position 85x55x h 80 cm 33 1/2"x21 5/8"x h 31 1/2" | 📏 | 57 Kg 125.5 lbs | 📏 | 88x69x h 97 cm 34 1/2"x27"x h 38" | 📏 | 69 Kg 152 lbs |

ACCESSORI E DISCHI RICAMBI - ACCESSORIES AND SPARE DIAMOND DISC

| Articolo Part no. | Descrizione - Description |
|---------------------|---|
| 431EP01A | Estensione piano lavoro per piastrelle di larghezza fino a 80 cm - Table side extension for tiles up to 80 cm (31 1/2") width |
| 179CC200 | Disco corona continua Ø 200 mm - Continuous rim diamond disc Ø 200 mm (8") |

